

EZ26 Technical specifications

Metric »

Imperial »

Operating data

Shipping weight	5,443 - 6,969 lb
Operating weight	5,668 - 7,191 lb
Biting force max.	3,439.6 lbf
Breakout force max.	5,058.2 lbf
Digging depth max.	108.1 in
Dumping height	111.9 - 121.6 in
Digging radius max.	189.4 in
Superstructure slewing speed	10.2 rev/min
L x W x H	168 x 62 x 95 in

Engine / Motor

Engine / Motor manufacturer	Yanmar
Engine / Motor type	3TNV76
Engine / Motor	water-cooled 3-cylinder diesel engine
Displacement	68.1 in³
RPM / speed	2,500 rpm
Engine performance output to ISO	20.4 hp
Battery	44 Ah
Tank capacity	38 US qt

Hydraulic system

Duty pump	double variable- & two-gear pump
Flow rate	8.14 US gpm
Max. flow rate	8.06 + 8.06 US gpm
Max. flow rate	5.34 + 1.9 US gpm
Operating pressure for working and traction hydraulics	3,263.4 psi
Operating pressure slewing gear	2,987.8 psi

Undercarriage

Travel speed max.	2.36 mph
Chain width	11.8 in

Ground clearance	10.9 in
Dozer Blade	
Width	61.9 in
Height	11.4 in
Stroke max. above ground	15 in
Stroke max. below ground	16.5 in
Sound level	
Sound level (LwA) acc. to 2000/14/EC	93 dB(A)
Cabin - specified sound pressure level LpA acc. to ISO 6394	79 dB(A)